


































THERMATEX[®] Aquatec Medical

Features

- THERMATEX Aquatec Medical ceilings provide the optimal acoustical ceiling for high humidity areas of up to 100% RH
- Provides excellent sound absorption for enhanced acoustic comfort (NRC 0.90)
- Damage resistant, washable, smooth laminated surface
- High light reflective finish (LR 0.88)
- ISO 3 Clean Room Performance
- Anti-microbial performance provides protection against bio-contamination
- 3rd party certified sustainable performance
- The ideal solution for hygiene and healthcare environments, swimming or hydrotherapy pools, laboratories, locker or shower areas



THERMATEx® Aquatec Medical

	Panel Options	Board	Tegular 24/90	Tegular 15/90															
 Edge details																			
 Dimensions (mm)	600 x 600 x 19mm	BP6890G	BP6892G	BP6894G															
	1200 x 600 x 19mm	BP6891G	BP6893G	BP6895G															
	1. Special items and other sizes available upon request. 2. For all items: Contact your local AMF Distributor representative for stock availability.																		
 Suspension systems	Shall be AMF: Prelude 24mm steel T-Bar, or Slimline 15mm steel T-Bar Grid. Note: Contact your AMF Distributor for aluminum grid systems for pool applications																		
 Weight	5.2 kg/m ²																		
 Colour	White																		
 Sound absorption	<table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_P</td> <td>0.60</td> <td>0.70</td> <td>0.85</td> <td>0.90</td> <td>1.00</td> <td>1.00</td> </tr> </tbody> </table> NRC = 0.90 as per EN ISO 354 & EN ISO 11654			Frequency f (Hz)	125	250	500	1000	2000	4000	α_P	0.60	0.70	0.85	0.90	1.00	1.00	 * NRC = 0.90	
Frequency f (Hz)	125	250	500	1000	2000	4000													
α_P	0.60	0.70	0.85	0.90	1.00	1.00													
 Sound attenuation	EN ISO 10848-2 CAC = 29 dB as per EN ISO 717-1																		
 Fire resistance	Conforms with NCC Spec. C1.10 as tested to AS 5637.1:2015 - Group 1, and ISO 5660 - Group 1 - S																		
 Light reflectance	88%																		
 Thermal resistance	R-Value = 0.48 m ² K/W as per EN 12667																		
 Humidity resistance	RH100																		
 Clean room	ISO 3 as per ISO 14644-1																		
 Indoor air quality	 A+  E1  IACG	Durability / Cleanability  Scratch resistance  Hygiene performance  Washable and scrubable to ASTM D2486 (modified)																	
 Sustainability	 35%  ISO 14001  EPD  BIO-SOLUBLE WOOL  BLUE ANGEL  CRADLE TO CRADLE  GREEN BUILDING																		
Specifications	<ul style="list-style-type: none"> Ceiling system shall comprise AMF Thermatex Aquatec Medical. Panels shall achieve NRC 0.90, CAC 29, RH100 and Clean Room ISO 3. 		<ul style="list-style-type: none"> Panels certified for Green Star and WELL Building. Nominal size 600x600x19mm / 1200x600x19mm with Board edge / Tegular 24/90 edge / Tegular 15/90 edge. 		<ul style="list-style-type: none"> Suspension system shall be AMF Prelude XL 24mm Exposed Tee System / Slimline 15mm Exposed Tee System 														

Contact

p. +61 2 8198 9900
 e. info@amfceilings.com.au
 w. amfceilings.com.au

©2023 Australian Mineral Fibre (AMF) Pty Ltd
 Produced 15 February 2023

