



THERMATEX®



























Feinstratos Micro & Feinstratos Micro Complete

Features

- THERMATEX Feinstratos Micro ceilings provide good acoustical performance:
 - Sound absorption up to 0.70
 - Sound attenuation up to 35dB
- Fine textured, micro-perforated surface that creates an even, uniform ceiling appearance
- High light reflective finish (LR 0.85)
- Available in a range of edge profiles and sizes
- Sustainable performance
- Ideal for offices, retail stores, libraries and classrooms



THERMATEX® Feinstratos Micro & Feinstratos Micro Complete

	Panel Options	Board	Tegular 24	Tegular 15					
 Edge details									
 Dimensions (mm)	Feinstratos Micro								
	600 x 600 x 15mm	BP6720G	BP6722G	*					
	1200 x 600 x 15mm	BP6721G	BP6723G	*					
	Feinstratos Micro Complete								
	600 x 600 x 15mm	BP6760G	BP6762G	*					
1200 x 600 x 15mm	BP6761G	BP6763G	*						
	* Special items and other sizes available upon request. For all items: Contact your local AMF Distributor representative for stock availability.								
 Suspension systems	Shall be AMF: Prelude 24mm steel T-Bar, or Slimline 15mm steel T-Bar								
 Weight	4.0 kg/m ²		Colour	White					
 Sound absorption	Frequency f (Hz)	NRC	125	250	500	1000	2000	4000	
	αP Feinstratos Micro	0.60	0.50	0.50	0.55	0.70	0.65	0.50	
	αP Feinstratos Micro Complete	0.70	0.45	0.65	0.70	0.80	0.75	0.50	
	NRC as per EN ISO 354 & EN ISO 11654								
 Sound attenuation	EN ISO 10848-2 CAC = 35 dB as per EN ISO 717-1								
 Fire resistance	Conforms with NCC Spec. C1.10 as tested to AS 5637.1:2015 - Group 1, and ISO 5660 - Group 1 - S								
 Light reflectance	85%								
 Thermal resistance	R-Value = 0.40 m ² K/W as per EN 12667								
 Humidity resistance	RH95								
 Indoor air quality				Cleanability					
	A+	E1	IACG	Wipeable					
 Sustainability									
	40%	Green Star	EPD	Biodurable Wool	Blue Angel				
Specifications	<ul style="list-style-type: none"> Ceiling system shall comprise AMF Thermatex Feinstratos Micro / Feinstratos Micro Complete. Panels shall achieve NRC 0.60 / 0.70, CAC 35. 		<ul style="list-style-type: none"> Panels certified for Green Star. Nominal size 600x600x15mm / 1200x600x15mm with Board / Tegular 24 edge / Tegular 15 edge. 		<ul style="list-style-type: none"> Suspension system shall be AMF Prelude XL 24mm Exposed Tee System / Slimline 15mm Exposed Tee System. 				

Contact

p. +61 2 8198 9900
e. info@amfceilings.com.au
w. amfceilings.com.au

©2023 Australian Mineral Fibre (AMF) Pty Ltd
Produced 15 March 2023

